


Smart choice for power

xantrex

Get connected with Xantrex's new Grid Tie Solar Inverters



Xantrex inverters make installation easy and affordable

When Xantrex set out to develop the Grid Tie Solar Inverters we listened to the experts – renewable energy dealers and installers. The result is a high performance inverter that makes utility interactive installations easier and more cost effective. Our high performance PV string inverters offer high efficiency, lower installed cost, improved aesthetics and high reliability. The GT Series inverters are high quality products that offer the best price/performance ratio in the industry.

High Performance String Inverters:

- ▶ Superior PV energy harvest
- ▶ Peak inverter efficiency
- ▶ Excellent thermal performance

Easy and Affordable to Install:

- ▶ Wide PV input MPPT tracking voltage range makes module selection and sizing extremely flexible
- ▶ Includes a lightweight and versatile mounting bracket that simplifies installation
- ▶ Modular design allows inverters to be mounted side-by-side
- ▶ Lightweight and compact size
- ▶ Rugged IP54 inverter enclosure allows reliable outdoor and indoor installations

Full Featured Inverter Display and Communications:

- ▶ Liquid Crystal Display (LCD)
- ▶ LCD vibration sensor allows the tap of a finger to turn backlight on and display screen cycling
- ▶ Bright LED indicators provide system status at a glance
- ▶ PC software for remote monitoring and system troubleshooting



Xantrex Technology Inc.

Headquarters
8999 Nelson Way
Burnaby, British Columbia
Canada V5A 4B5
800 670 0707 Toll Free
604 420 1591 Fax

Edificio Diagonal 2A,
C/ Constitución 3, 4º 2ª
08960 Sant Just Desvern
Barcelona, Spain
+34 93 470 5330 Phone
+34 93 473 6093 Fax
europesales@xantrex.com

www.xantrex.com

Xantrex GT Series Inverters

Electrical Specifications	GT 2.5DE	GT 3.8DE
Maximum AC Power Output	2500 W	3800 W
Nominal AC Power Output	2300 W	3500 W
AC Voltage (nominal)	184 to 264.5 VAC (230 VAC)	184 to 264.5 VAC (230 VAC)
AC Frequency (nominal)	47.0 to 50.2 Hz (50Hz)	47.0 to 50.2 Hz (50Hz)
DC Input Voltage Range	195 to 600 VDC	195 to 600 VDC
Peak Power Tracking Voltage Range	195 to 550 VDC	195 to 550 VDC
Current THD	<3%	<3%
Peak Inverter Efficiency	95.0% (includes transformer)	95.30% (includes transformer)
Euro Efficiency	94.0% (includes transformer)	94.50% (includes transformer)
Maximum Continuous Output Current	12.5 AAC	19 AAC
Over Current Protection	15 A	20 A
Night Time Tare Loss	1 W	1 W
Regulatory Compliance	CE marked according to the following EU directives and standards: EMC Directive: EN 61000-6-1, EN 61000-6-3, EN61000-3-2, EN61000-3-3 Low Voltage Directive: EN 50178	
Other Approvals	BGFE Certified to VDE0126	BGFE Certified to VDE0126
Mechanical Specifications		
Operating Temperature Range	-25 °C to +65 °C (-13 °F to +149 °F)	-25 °C to +65 °C (-13 °F to +149 °F)
Enclosure Type	IP54	IP54
Unit Weight	20 kg	20.5 kg
Shipping Weight	26 kg	26.5 kg
Inverter Dimensions (H x W x D)	59.7 cm x 40.3 cm x 13.6 cm	59.7 cm x 40.3 cm x 13.6 cm
Mounting	Wall Mount (mounting bracket included)	Wall Mount (mounting bracket included)
Features		
Cooling	Convection (no fan required)	Convection (no fan required)
Display	Backlit, 2-line, 16-character Liquid Crystal Display	Backlit, 2-line, 16-character Liquid Crystal Display
Communications	RS 232 and 2 Xantrex RJ45 ports	RS 232 and 2 Xantrex RJ45 ports
Warranty	5-year parts & labor (10-year extended warranty available)	5-year parts & labor (10-year extended warranty available)
Part Number/Model Number	864-0106	864-0103