



# Poly 200W

## Features

- High conversion efficiency
- Low power tolerance of 0~+3%
- Low degradation under light exposure
- Can withstand high wind-pressure, snow load and extreme temperature
- Passing IEC 61215 2400Pa mechanical load test

## Quality and Safety


- 10-year warranty on product materials and processing technology
- Power output warranty:10 years:90%,25 years:80%
- ISO 9001:2008(Quality Management System) certified factory
- IEC61215,IEC61730 ,MCS CEC certified products
- TUV,CE conformity

## Applications

- On-grid residential roof-tops
- On-grid commercial/industrial roof-tops
- Solar power plants
- Off-grid system
- Other on-grid applications

## Specifications

Model Type	SIP200-24
Peak Power(Pmax)	200,00
Maximum Power Voltage(Vmp)	36,50
Maximum Power Current(Imp)	5,48
Open Circuit Voltage(Voc)	43,80
Short Circuit Current(Isc)	5,84
Cells Efficiency(%)	17,48
Module Efficiency(%)	15,18
Maximum System Voltage(V)	1000
Maximum Series Fuse Rating(A)	10
Power Tolerance	0~+3%
Pmax Temperature Coefficients(W/°C)	-0.450%
Voc Temperature Coefficients(V/°C)	-0.350%
Isc Temperature Coefficients(A/°C)	+0.040%
NOCT Nominal Operating Cell Temperature(°C)	47±2
Operating and Storage Temperature(°C)	-40~+85
Standard Test Condition(STC)	1.000W/m²;AM 1.5;25+/-2°C



## Mechanical characteristics & Packaging

Cell Type	Poly-crystalline 156×104mm
No. of Cells	72(6×12)
Dimensions	1330×990×35mm
Weight	16.40kgs
Front Glass	3.2mm high transmission,low iron,tempered glass
Frame	Anodized Aluminium Alloy
Junction box	IP65 Rated
Output cables	2.5mm² Length 90cm, MC4 connector
Quantity/cartons	2pcs

## Dimensions

200W多晶硅太阳能电池板 (1330\*990\*35)  
200W Poly solar panel (1330\*990\*35) 单位:mm Unit:mm

